
MAXWELD

MAXWELD 711 PVC PVC Heavy Duty Solvent Cement



MAXWELD 711 PVC Cement

MAXWELD 711 PVC is a heavy bodied, heavy duty, industrial grade, low VOC clear emission, medium setting, high strength cement for all classes and schedules of PVC pipe and fittings with interference fit through 12 inch diameter. It has a good gap filling property and its medium set allows more working time in warm weather conditions.

Advantages of MAXWELD 711 PVC Cement-

- ☑ Heavy bodied solvent cement
- ☑ High strength solvent cement for PVC pipes and fittings
- ☑ Medium setting solvent cement
- ☑ Good gap filling properties
- ☑ Low VOC emission solvent
- ☑ Shelf life of 2 years in tight sealed packing

Application Areas-

- Formulated for use on all types of PVC plastic pipe applications
 - Formulated for use in potable, drain, sewer, irrigation and vent applications
 - Residential / Commercial, mobile homes and industrial piping systems
 - Solvent cement for PVC plastic pipes of Type I & Type II
-

Direction for Use-

Do not thin or mix with any other solvent. 1. Apply liberal coat of cement to pipe to the depth of the socket, leave no surface uncoated. 2. Square pipe ends remove all burs and dirt. Recommended applicator for pipe over 3" is a brush ½ the diameter of the pipe. 3. Apply thin coat to fitting, avoid puddling of cement. 4. Assemble parts QUICKLY. Cement must be FLUID, if not so re-coat both surfaces. To fit, push bottoms. 5. Hold pipe and fitting together for about 60 seconds. Allow joint to cure sufficiently before handling. Do not pressure test until cement is fully cured. To avoid evaporation, the lid must be tightly CLOSED after each usage and must be used as quickly as possible once opened.

Packing Available-

Supplied in 50 mL, 118 mL and 237 mL packing

Precautions-

Do not breathe vapours. Use only in well ventilated areas (open doors and windows nearby). Do not use or store near heat, sparks or flames. Do not smoke when using. Wear safety glasses with side shields and rubber gloves while using. May cause coughing, sore throat, difficult breathing, headache, dizziness or nausea – get fresh air. If swallowed, DO NOT INDUCE VOMITING. Drink water and seek medical attention immediately. In case of contact with eye or skin, flush thoroughly with water.

Warning-

EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. MAY IRRITATE EYES AND SKIN. VAPOR HARMFUL – MAY IRRITATE RESPIRATORY TRACT AND CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. HARMFUL OR FATAL IF SWALLOWED. READ LABEL CAREFULLY PRIOR TO USE.

NOTE- Bharat Chemicals solvent cement products must never be used in a PVC systems using or being tested by compressed air or gases; including air-over-water booster.



Manufactured by:

BHARAT CHEMICALS

Tighra, Satna 485001 (M.P.) India

Website- www.bharat-chemicals.com

Website- www.multiproof.co.in

Email- info@bharat-chemicals.com

Email- info@multiproof.co.in

Mob- +91-9425172928; +91-9827203883



An ISO 9001:2008 Certified Company

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products